TECHNICAL DATA SHEET

Aqmos R2D2-32 Waterontharder

No Installation Kit / Met drukverhoger

INTEGRATED SOFTENERS

1-3 personen

Article number	**test1**
Please choose:	**No Installation Kit**
Accessoires ofzo	**Met drukverhoger**
Warranty	**5 + 5 year warranty**

FOR	CAPACITY	FOOTPRINT	SALT REFILL
1-3 persons	**3,200** L at 7.5 °dH	**22 x 46** cm	**3-5** months

TECHNICAL SPECIFICATIONS

TECHNICAL DATA

Softening Capacity (at 7.5°dH)	**3,200 L**
Salt consumption per liter of Resin	**160-200 grams**
Salt consumption per regeneration	**1.6 kg**
Service flow rate	**1,0 m³/h**
Operating pressure	**2-6 bar**
Pressure loss at max. flow	**0,6 bar**
Max. water temperature	**30 °C**

EXTRA

Series	**R2D2**
Number of people	**1 person**

CONTROL VALVE

Water connection type	**3/4" OD 90° elbow**
Drain connection type	**12 mm**
Power connection type	**230/ 50/24 V**
Power consumption	**3 watts**
Control valve	**BNT1650**
Regeneration duration	**75 minutes**

MEASUREMENTS

Resin Lifespan	**30 years**
Resin Volume	**8 L**
Salt tank capacity	**25 kg**
Length	**46 cm**
Width	**22 cm**
Height	**65 cm**
System weight	**17 kg**

WHAT'S INCLUDED

1 x	AQMOS R2D2-32 water softener
2 x	BSPT connector 3/4" 90°
1 x	12 V power adapter
1 x	Manual
1 x	Pressure booster 1.2 bar
1 x	Wall bracket for pressure booster

DIMENSIONS