TECHNICAL DATA SHEET

Ecosoft PINK-10

No Installation Kit / None

INTEGRATED SOFTENERS

x-x persons

Please choose:	**No Installation Kit**
Options:	**None**
Warranty	**Manufacturer's warranty**

TECHNICAL SPECIFICATIONS

TECHNICAL DATA

Softening Capacity (at 7.5°dH)	**3.7 m³**
Salt consumption per liter of Resin	**100 grams**
Salt consumption per regeneration	**1.0 kg**
Service flow rate	**1.2 m³/h**
Operating pressure	**2-6 bar**
Pressure drop in service mode	**0.5 bar**
Water temperature	**+4...+30 °C**

EXTRA

Series	**Pink**
Number of people	**1-3 persons**

CONTROL VALVE

Water connection type	**¾" OD straight**
Drain connection type	**½" OD or 12 mm**
Power connection type	**230/ 50/24 V**
Power consumption	**30 watts**
Control valve	**Clack® WS1DV**
Regeneration duration	**75 minutes**

MEASUREMENTS & VOLUMES

Resin Lifespan	**30 years**
Resin Volume	**10 L**
Salt tank capacity	**12.5 kg**
Length	**43 cm**
Width	**27 cm**
Height	**47 cm**
System weight	**16.2 kg**